

Huawei.Pre.H11-851\_V3.0.VCEplus.40q - DEMO

Number: H11-851\_V3.0  
Passing Score: 800  
Time Limit: 120 min



**Exam Code:** H11-851\_V3.0  
**Exam Name:** HCIA-Video Conference V3.0  
**Website:** [www.VCEplus.io](http://www.VCEplus.io) - [www.VCEup.com](http://www.VCEup.com)

VCEup

**QUESTION 1**

In the case of multiple MCUs cascading, the () feature enables the upper venue to browse the lower venue screen across levels.

- A. Intelligent secondary flow adaptation
- B. Network Remote Recording
- C. Multi-channel cascade
- D. End-cloud collaboration

**Correct Answer:** C

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 2**

() Does not belong to the three elements of video conferencing multimedia business.

- A. Sound
- B. Data
- C. Image
- D. Network

**Correct Answer:** D

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 3**

() The message indicates that the request cannot be implemented on any SIP server.

- A. 6xx
- B. 5xx
- C. 1xx
- D. 3xx

**Correct Answer:** A

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 4**

For the response message "3xx", it means ?().

- A. The server has received the request message and is processing it.
- B. The server must take further action to complete the request.
- C. The request was received, processed, and successfully accepted.
- D. Indicates that the SIP server failure could not complete the processing of the correct message

**Correct Answer:** B

**Section:** (none)

**Explanation**

www.VCEplus.io

**Explanation/Reference:**

Explanation:

**QUESTION 5**

Regarding wireless access, the following description is correct? ().

- A. CloudLink endpoints support enabling both clients and hot-spots, and only support 2.4GHz wireless communication.
- B. After the CloudLink terminal enables the WiFi client, it supports automatic scanning and connection of wireless access points, supports static setting of IP addresses, and cannot be dynamically obtained.
- C. CloudLink terminal, when WiFi clients are enabled, support automatic scanning and connection of wireless access points, and support dynamic ip address acquisition , which cannot be modified manually.
- D. When the CloudLink terminal enables the WiFi hot-spot, the PC can connect directly to the hot-spot without cables and connect to the wireless network

**Correct Answer:** D

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 6**

During SVC conferencing, the terminal sends up to 4 video streams to the C1oudMCU/VP98 series NCU, including ().

- A. Secondary flow 2 way, Feng flow 2 way
- B. Mainstream 4 each
- C. Subflow 1 way, mainstream 3 way
- D. Secondary 3-way, mainstream 1-way

**Correct Answer:** C

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 7**

SMC3.0 is managed over the () protocol for IdeaHub.

- A. SNMP
- B. TR069
- C. Telnet
- D. SSH

**Correct Answer:** A

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 8**

Regarding CloudMCU multi-stream conferencing, the following description is incorrect?().

- A. Multi-stream hybrid conferencing supports AVC and SVC terminal access, supports cascading with fully adaptable conferences, and also supports cascading with multi-stream hybrid conferencing.
- B. Pure SVC conferencing consumes more resources than AVC conferencing.
- C. Compared to AVC conferencing, the codec is done by the terminal side in the SVC conferencing, and the NCU is only responsible for forwarding.
- D. Multi-stream meetings do not support multi-screen broadcasting.

**Correct Answer:** D

**Section:** (none)

**Explanation**

www.VCEplus.io

**Explanation/Reference:**

Explanation:

**QUESTION 9**

Regarding SMC3.0 conference control, the following statement is incorrect?().

- A. In SIC3.0, only the meeting administrator and the chairman are allowed to control the meeting, and other terminals are only allowed to apply for the chairman and speak.
- B. SMC3.0 does not support the operation of recording and broadcasting conferences.
- C. SMC3.0 divides the control into meeting control and venue control, and the venue control is lowered to the shortcut menu and the right health menu of the venue list.
- D. SMC3.0 supports continuous roll call, multi-screen setting, auxiliary stream transmission and other controlled operations.

**Correct Answer:** B

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 10**

Regarding the description of meeting administrators and regular users of SMC3.0, the following error is ?()

- A. Meeting administrators and regular users support creating multi-level meetings.
- B. Meeting administrators and regular users support managing personal information.
- C. Meeting administrators and Syton users support creating meeting templates.
- D. Meeting administrators and regular users support creating data meetings.

**Correct Answer:** A

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 11**

CloudRSE supports on-demand and watching live streams over the Web, MP4 files generated by recording meetings can be on-demand via the () protocol, and ongoing live meetings can be played via ( Live Streaming Agreement

- A. HIIPS; HLS
- B. RTP; HLS
- C. HLS; HITPS
- D. HIIPS; RTP

**Correct Answer:** A

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 12**

The following is () that belongs to the video conferencing data transmission standard protocol. /

- A. G711
- B. T120
- C. MPEG-4
- D. H264

**Correct Answer:** B

**Section:** (none)

www.VCEplus.io

**Explanation****Explanation/Reference:**

Explanation:

**QUESTION 13**

114.1080p image pixels are equivalent to ().

- A. 16CIF
- B. 9CIF
- C. 20CIF
- D. 25CIF

**Correct Answer:** C

**Section:** (none)

**Explanation****Explanation/Reference:**

Explanation:

**QUESTION 14**

The video resolution of 115.1080p is ().

- A. 1920\*1080
- B. 720\*1080
- C. 1000\*1920
- D. 1080\*720

**Correct Answer:** A

**Section:** (none)

**Explanation****Explanation/Reference:**

Explanation:

**QUESTION 15**

Te terminals hold 1080p 30fps meetings and require at least () bandwidth.

- A. 2Mbps
- B. 512Kbps
- C. 1.5Mbps
- D. 1Mbps

**Correct Answer:** B

**Section:** (none)

**Explanation****Explanation/Reference:**

Explanation:

**QUESTION 16**

Regarding the VPT300 picture-in-picture display, the following description is incorrect?().

- A. The picture-in-picture display is turned off, and the close-up screen is rendered in full screen during close-up tracking.
- B. Picture-in-picture settings affect how it is rendered in auto-track mode.
- C. VPT300 supports setting the picture-in-picture display mode, the small screen size is fixed, and the position is fixed to the upper right corner.
- D. The picture-in-picture display is turned on, and the holy screen presents a panoramic view of the meeting when close-up tracking, and the small screen presents a close-up

**Correct Answer:** C

www.VCEplus.io

**Section: (none)**

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 17**

Regarding IdeaHub factory reset, the following description error is ?().

- A. On a factory reset, you can choose to keep your current IP address in the web interface.
- B. When the system is powered on normally, press and hold the reset button for 15 seconds to restore the factory settings.
- C. During device startup, press and hold the reset button for 15 seconds to restore the factory settings.
- D. After the factory reset, the local address book, call logs, meeting templates, history, etc. will be deleted and cannot be restored.

**Correct Answer: C**

**Section: (none)**

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 18**

() Support for creating meetings and joining meetings via IVR.

- A. VP9850
- B. VP9860
- C. VP9660
- D. C1oudMCU

**Correct Answer: C**

**Section: (none)**

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 19**

The CloudMcu supports floating 1license management, where 1 socket 1080p30 is fully adapted and can be converted to () channels Svc port.

- A. 24
- B. 12
- C. 8
- D. 6

**Correct Answer: C**

**Section: (none)**

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 20**

SMC3.0 provides device management capabilities that can manage up to () MCUs.

- A. 512
- B. 250
- C. 100
- D. 600

www.VCEplus.io

**Correct Answer:** A  
**Section:** (none)  
**Explanation**

**Explanation/Reference:**  
Explanation:

**QUESTION 21**

Regarding the C1oudRSE multipoint recording feature, the following description is incorrect?().

- A. During multipoint meeting recording, support meeting administrators to control recording and broadcasting on the SWC3.0 platform, such as suspending recording, resuming recording, and stopping recording.
- B. A SIP call is established between CloudRSE and the MCU, and the MCU sends an RTP stream to C1oudRSE, C1oudRSE Convert RIP streams into videos that can be streamed and streamed.
- C. Once CloudRSE is called into a multi-party conference by the MCU, it is only recorded according to the MCU's video switching policy, and cannot be recorded in SMC3.0 Record on any venue or multiview in a specified meeting.
- D. CloudRSE supports single-stream and multi-stream recording under multi-point video conferencing networking.

**Correct Answer:** C  
**Section:** (none)  
**Explanation**

**Explanation/Reference:**  
Explanation:

**QUESTION 22**

Te HD terminal remote loopback includes ().

- A. The secondary loopback
- B. VGA does not return to
- C. Video loopback
- D. Audio Ring

**Correct Answer:** ABCD  
**Section:** (none)  
**Explanation**

**Explanation/Reference:**  
Explanation:

**QUESTION 23**

When you are in a multi-stream meeting, you can switch the () layout type.

- A. Gallery view
- B. Speaker view
- C. Side-of-picture view
- D. Picture-in-picture view

**Correct Answer:** ABD  
**Section:** (none)  
**Explanation**

**Explanation/Reference:**  
Explanation:

**QUESTION 24**

IdeaHub supports screen casting via ().

- A. USB wired
- B. IdeaShare Key
- C. IdeaShare Wireless
- D. HDMI wired

www.VCEplus.io

**Correct Answer:** BCD  
**Section: (none)**  
**Explanation**

**Explanation/Reference:**  
Explanation:

**QUESTION 25**

Regarding the SMC 2.0 organization management function, the following statement is correct?().

- A. After SMC2.0 is installed, a root node is automatically created in the organization with the default name "Root".
- B. The functions of SMC2.0 are based on the organizational structure, and complete business functions are provided within each organizational structure, including user permissions, MCUs, venues, conference templates, conference scheduling, conference control, and
- C. An organization can contain multiple devices, and the same device can be subordinate to multiple organizations.
- D. A user can be assigned to multiple organizations, and users in different organizations can have different permissions.

**Correct Answer:** ABCD  
**Section: (none)**  
**Explanation**

**Explanation/Reference:**  
Explanation:

**QUESTION 26**

By default, the SMC3.0 system supports three roles, namely ().

- A. Meeting Administrator
- B. Normal User
- C. System Administrator
- D. Meeting Organizer

**Correct Answer:** ABC  
**Section: (none)**  
**Explanation**

**Explanation/Reference:**  
Explanation:

**QUESTION 27**

SMC3.0 uses a database and operating system () respectively.

- A. openEuler
- B. Windows Server
- C. GaussDB
- D. Microsoft SQL

**Correct Answer:** AD  
**Section: (none)**  
**Explanation**

**Explanation/Reference:**  
Explanation:

**QUESTION 28**

When adding a CloudRSE recording server to the SMC3.0 platform, you need to configure the () parameter in the CloudRSE web interface.

- A. Ip address
- B. SMC3.0 ip address of the

www.VCEplus.io



- C. SC of the docking username and password
- D. MCU's IP address

**Correct Answer:** ABC

**Section: (none)**

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 29**

The following are the characteristics of Huawei terminals ( ).

- A. WiFi connection
- B. The main call is Call set
- C. Multi-vision
- D. Voice Assistant

**Correct Answer:** ABCD

**Section: (none)**

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 30**

() An entity that is defined by the H.323 Agreement.

- A. Terminal
- B. MCU (Multipoint Conference Control Unit)
- C. GK (Gatekeeper).
- D. Gateway

**Correct Answer:** ABCD

**Section: (none)**

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 31**

1 Transactions must contain a () part.

- A. A final response
- B. Zero or more temporary responses to
- C. A request message
- D. ACK

**Correct Answer:** ABC

**Section: (none)**

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 32**

Regarding "multipoint meetings", the following description is correct?().

- A. After a peer-to-peer call is established, you can set up a multipoint conference by calling other terminals point by point.

www.VCEplus.io

- B. The terminal convenes a multipoint meeting and needs to use the MCU as the meeting convening resource.
- C. Multipoint conferencing supports hybrid H323 and SIP conferencing.
- D. A multi-point meeting is a meeting convened in three or more venues.

**Correct Answer:** ABCD

**Section: (none)**

**Explanation**

**Explanation/Reference:**

Explanation:

#### QUESTION 33

Regarding the gallery view in a multi-stream meeting, the following description error is ?().

- A. In a multi-stream meeting, if you select Gallery View, the screens are presented in the following order of precedence: broadcast venue video> speaker video> other venue video.
- B. In a multi-stream meeting, if you select Gallery view, you can display up to 16 videos or share a presentation.
- C. In a multi-stream meeting, if you select Gallery View, the picture is presented in a large number of small ways.
- D. In a multi-stream meeting, if you select Gallery View, the answer is displayed equally for each venue video and shared presentation

**Correct Answer:** AD

**Section: (none)**

**Explanation**

**Explanation/Reference:**

Explanation:

#### QUESTION 34

Regarding the speaker view in a multi-stream meeting, the following description is correct?().

- A. In Speaker view mode, if there is a shared presentation in the meeting, the presentation image is displayed in a small screen.
- B. In Speaker View mode, if there is a shared presentation in the meeting, the presentation image is displayed in the larger screen.
- C. In Speaker view mode, if there is no shared presentation in the meeting, the large screen displays the speaker video, but the user cannot lock out a speaker video.
- D. In the speaker view mode, if the user broadcasts or selects to see the venue, the large screen will switch to the broadcast or the video of the venue that is selected to watch.

**Correct Answer:** BD

**Section: (none)**

**Explanation**

**Explanation/Reference:**

Explanation:

#### QUESTION 35

( ) is a multiviewer mode supported by the CloudMCU.

- A. Divided into 16 screens equally
- B. Divided into 24 screens
- C. A large number of small Ontable modes
- D. Equally 9 Screen

**Correct Answer:** ABCD

**Section: (none)**

**Explanation**

**Explanation/Reference:**

Explanation:

#### QUESTION 36

Regarding Cloud RSE, the following description is correct?().

- A. The CloudRSE power supply supports 1+1 hot backup, seamlessly switching to a backup power source in the event of a failure, ensuring consistent and reliable recording.
- B. CloudRSE supports both HD and SD resolutions, and can only be viewed on-demand and live on a pc.
- C. CloudRSE can provide video conferencing single-stream, dual-stream (video image + conference data sharing) recording and broadcasting.
- D. CloudRSE supports resource pool management, and The CloudRSE in the resource pool is mutually backupable, and the resource pools cannot be backed up to each other.

**Correct Answer:** ACD

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 37**

An HTTP connection is established between the SMC and the MCU, and selecting Support HTTPS indicates SMC and MCU Connections between them are in encrypted mode. ()

- A. True
- B. False

**Correct Answer:** A

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 38**

TE40 supports a PSTN interface where you can connect a phone to a conference over voice ().

- A. True
- B. False

**Correct Answer:** B

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 39**

You can adjust the white balance of the lens through the TE terminal to adjust the color display effect of the picture ().

- A. True
- B. False

**Correct Answer:** A

**Section:** (none)

**Explanation**

**Explanation/Reference:**

Explanation:

**QUESTION 40**

In SMC 2.0, the same venue and MCU cannot be added to more than one organization at the same time ().

- A. True
- B. False

**Correct Answer:** B

**Section:** (none)

www.VCEplus.io

**Explanation**

**Explanation/Reference:**  
Explanation:

[www.VCEplus.io](http://www.VCEplus.io)